Date	SYM	REVISION RECORD	AUTH	DR.	CK.
12/01/17	A	UPDATED SPECIFICATION	T.B.	B.S.	
04/12/19	B	UPDATED TO "ROHS COMPLIANT"	T.B.	B.S.	
11/26/19	C	WAS RATED 30AMP. ADDED WIRE LENGTH	T.B.	B.S.	
11/17/21	D	WAS 14 AWG	T.B	B.S	



NOTES:

1. MATERIAL:
HOUSING : NYLON PA66, UL 94-V2, UL FILE NO. E41938
2. Housing also in PA6 UL 94-HB,, UL#E36632
3. LEAD WIRE IN LOOP: 8" OVERALL LENGTH RED WIRE, 16 AWG, UL-1015, 600V, 105°C, FLAME RATING VW-1, UL FILE NO. E77961, OR ENGINEERING APPROVED EQUIVALENT
4. RATED CURRENT: 20A
5. ACCEPTS AGC/JMC FUSES
6. INSULATION RESISTANCE AT 500V DC: 100MΩ MIN
7. CONTACT RESISTANCE: 5mΩ AT 1A DC
8. DIELECTRIC STRENGTH FOR 60 SECONDS: AC 1500V MIN ROHS COMPLIANT
9. Wires + Overmold: DC 32V Max.
10. Contact/Terminal are brass without plating

Tolerance (Except as noted)	Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal ±.5 (.020)		Scale	Drawn By B.S. Approved By T.B.
Fractional ± .8 (.030)	Title INLINE FUSE HOLDER		
Angular ± 3°	Date 11/26/19	Drawing Number BF309	