

SOLDER LUG: STEEL, NICKEL PLATED. SPRING: SPRING STEEL, NICKEL PLATED LUGS: BRASS, NICKEL PLATED CONTACT RESISTANCE: UNDER $50m\Omega$ FOR +/- CONTACTS PER EIA-540J000 **ROHS 2 COMPLIANT**

FLAMMABILITY RATING -UL94-HB, UL FILE NO. E56070(S)

TEMPERATURE RANGE: -10°C to +100°C

Tolerance (Inches)	MPD MEMORY PROTECTION DEVICES	Memory Protection Devices, Inc					
	Centifiel Global Manufacturar of Electronic Components	200 Broad Hollow Road, Farmingdale, New York 11735					
Decimal				Scale	Drawn By B.S) i	
±.5 (.020)					Approved By	T.B.	
Fractional	Title 23A BATTERY HOLDER WITH SOLDER LUGS						
± .8 (.030)	ESH DHITEKT HULDER WITH SULDER LOUS						
Angular	Date	Drav	ving Nu	mber			
± 3°	06/26/25	5	Bl	H23AL			

REVISION RECORD

Date

11/15/03

MYZ

AUTH

T.B.

T.B.

T.B.

DR. CK.

B.S.

B.S.

B.S.