






Date	SYM	REVISION RECORD	AUTH	DR.	CK.
06/16/17	C	DIM. 159.00 WAS 160.00 DIM. 15.90 WAS 16.00	T.B.	B.S.	
06/01/26	D	DIM. 157.0 WAS 159.0 DIM. 15.80 WAS 15.90 DIM. 32.4 WAS 32.0	D.L.	B.S.	



NOTES:
 Plastic material - Polypropylene
 Flammability Rating -UL94-HB, UL File NO. E216959
 Temperature Range: -10°C to +100°C
 Wires: 26 AWG, UL 1007, CSA, TR-64, 300V, 80°C
 Springs - Nickel Plated Spring Steel
 Rivets - Brass, Nickel Plated
 CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER
 EIA-540J000
 ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
	decimal ±.5 (.020)	Scale	Drawn By B.S. Approved By D.L.
Fractional ± .8 (.030)	Title 2AA BATTERY HOLDER WITH WIRE LEADS		
Angular ± 3°	Date 06/01/26	Drawing Number BH362A	