



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
08/30/23	C	Added orientation note for snaps wires	D.L.	B.S.	
09/14/23	D	Changed the orientation of snaps	D.L.	B.S.	

**NOTES:**

1. I STYLE 2 PCS. MOLDED CASE CONSTRUCTION WITH CRIMP CONNECTIONS. CRIMP ON WIRE INSULATION AND ON WIRE PROVIDES STRAIN RELIEF THAT STANDARD SOLDERED SNAPS DO NOT HAVE.
2. ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY.  
RED WIRE TO POSITIVE CONTACT.  
BLACK WIRE TO NEGATIVE CONTACT.  
ROHS COMPLIANT

NO.	PART NAME	MATERIAL	QTY.	Tolerance (Except as noted)	MPD Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
1	COVER	PVC COVER OVER FIBERBOARD	1	decimal ±.5 (.020) Fractional ± .8 (.030) Angular ± 3°	Scale	Drawn By B.S.	
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1			Approved By T.B.	
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1		Title 9 VOLT BATTERY SNAP-I STYLE-4" WIRE LEADS		
4	FEMALE SNAP	BRASS, NICKLE PLATED	1		Date 09/14/23	Drawing Number BS4I	
5	MALE SNAP	BRASS NICKLE PLATED	1				