

- NOTES**
- COMPATABLE RECEPTICAL/SOCKETS
- PTS-22NL
 - PTS-2NL
 - PTF-2L


- MECHANICAL PROPERTIES
- MINIMUM PITCH: 2.54MM(0.100IN)
 - FULL STROKE: 6.4MM(0.252IN)
 - WORKING STROKE: 4.2MM(0.165IN)

- SPRING FORCES
- INITIAL SPRING LOAD: .59N(61GF)
 - 2/3 STROKE LOAD: 2.16N(220GF)


- MATERIALS
- PLUNGER: TOOL STEEL/ GOLD PLATE
 - SPRING: PIANO WIRE/ GOLD PLATE
 - BARREL: PHOSPHOROUS BRONZE/ GOLD PLAT

- ELECTRICAL PROPERTIES
- 5A MAX CURRENT

REVISIONS					
ECN	ZONE	REV.	DESCRIPTION	DATE	REVISED BY
-	-	A	INITIAL RELEASE	7/24/2026	-



ISO VIEW
TIP SHAPE



APPROVALS		DATE	MEMORY PROTECTION DEVICES, INC. Certified Global Manufacturer of Electronic Components 200 Broadhollow Road, Suite 4 Farmingdale, NY 11735 (631) 249-0001 / Fax (631) 249-0002 www.memoryprotectiondevices.com		
DRAWN	JV	7/24/2026			
CHECKED					
DO NOT SCALE DRAWING			TITLE: Pogo Pins PTP-2L Series_Knife Edge		
SIZE A		DWG NO. MPD-PTP-2PE1L-3GA	REV A		
SCALE: 4:1		SHEET: 1 OF 1			